### **Data Sheet**






Conwed Baffles bring the performance you expect from a world-class acoustic solution to the growing trend of baffles. Combined with the Conwed Express Hanging System, any space can be perfectly fitted with highly customizable baffles.

Respond Series

# Items to specify



Fire rating

Conwed products meet or exceed ASTM E84 standards for smoke development and flame spread on a component level.

Shapes

This product can be made into custom shapes for complex designs. Contact Customer Service for more info on how we can support your project.



Washable

Mounting type

Fabric partners

Designtex

a.

Preinstalled connection points ready

Conwed Express Hanging System is

Carnegie kvadrat Guilford of Maine

Kno

for suspension hardware

an optional add-on

Refer to the Maintenance & Cleaning Guide for more details. conwed.com/cexpmaintenanceandcleaning Hotmelt fabric adhesion

Provides superior bond strength lasting the lifetime of the product. Easily reactivated for field repairs and modification.

### Corners



#### Edge profile Half bevel Square Radius

maharam

Sustainability

For your LEED projects, our products can help you qualify for different points depending on the product you choose. Contact us to learn more detailed information. To view our certificate visit conwed.com/cexp-LEED.

## Warranty

3 years. Refer to Warranty for more details. conwed.com/cexpwarranty

### Max size availabilities

- Standard core max size
- NAF (No-Added-Formaldehyde core) max size

Thickness	4'×10'	5'×10'		
2"	0	•		
3"	•			
4"	0	•		

Minimum height of 6"

## Acoustic performance

The NRC of the products are determined from an average of sound absorption coefficients, obtained from tests conducted according to ASTM C423 procedures in an NVLAP accredited laboratory.

HZ →	125	250	500	1000	2000	4000	NRC ↓
2"	—	—	—	—	—	—	—
3"	—	—	—	—	—	—	—
4"	—	—	—	—	—	—	—

VFTFRAN

**Click for latest document version** conwed.com/datasheet-baffle-fabric-a