

All products made-to-order

Ceiling Panel | Fabric


Finish



Conwed Panels are reliable, all-purpose acoustic solutions. Capable of multiple levels of durability, highly-customizable finishes, and mounting options, this product is suitable for schools, auditoriums, theaters, offices, and libraries: anywhere noise control is needed.

Respond Series

Items to specify







Click for full specsheet conwed.com/specsheet-ceilingpanel-fabric-hi

Mounting type



Rotofast

Snap-on

Anchors



Resin





Hotmelt fabric adhesion

Provides superior bond strength lasting the lifetime of the product. Easily reactivated for field repairs and modification.

Corners



Square

Fabric partners

Carnegie kvadrat Guilford of Maine **DesignTex** maharam

Edge profile



Square

Fire rating

Conwed products meet or exceed ASTM F84 standards for smoke development and flame spread on a component level.



Shapes



Washable

Refer to the Maintenance & Cleaning Guide for more details.

conwed.com/cexpmaintenanceandcleaning



Sustainability

For your LEED projects, our products can help you qualify for different points depending on the product you choose. Contact us to learn more detailed information.

To view our certificate visit conwed.com/cexp-LEED.



Warranty

3 years. Refer to Warranty for more details

conwed.com/cexpwarranty

Max size availabilities

- Standard core max size
- NAF (No-Added-Formaldehyde core) max size

Thickness	4'×8'
] 1/16"	• •
2 1/16"	• 0
3 1/16"	• •

Minimum size of 12"x12"

Acoustic performance

The NRC of the products are determined from an average of sound absorption coefficients, obtained from tests conducted according to ASTM C423 procedures in an NVLAP accredited laboratory.

HZ →	125	250	500	1000	2000	4000	NRC ↓
1 1/16"	0.13	0.45	0.93	1.07	1.06	1.00	0.90
2 1/16"	0.26	0.87	1.09	1.03	1.01	1.05	1.00
3 1/16"	0.32	0.95	1.09	1.06	1.03	1.00	1.05