

### All products made-to-order

# **Ceiling Panel** | Fabric

Product


Finish Durability

**Respond Series** 

Tackable surface

Conwed Panels are reliable, all-purpose acoustic solutions. Capable of multiple levels of durability, highly-customizable finishes, and mounting options, this product is suitable for schools, auditoriums, theaters, offices, and libraries: anywhere noise control is needed.

# Items to specify



Click for full specsheet conwed.com/specsheet-ceilingpanel-fabric-ir

### Mounting type



Rotofast

Snap-on

Anchors







### Hotmelt fabric adhesion

Provides superior bond strength lasting the lifetime of the product. Easily reactivated for field repairs and modification.

### Corners





Radius Square

### Fabric partners

Carnegie kvadrat Guilford of Maine **DesignTex** maharam

### Edge profile









### Fire rating

Conwed products meet or exceed ASTM F84 standards for smoke development and flame spread on a component level.



### **Shapes**

into custom shapes for complex designs. Contact Customer Service for more info on how we can support vour project.



### Washable

This product can be made Refer to the Maintenance & Cleaning Guide for more details. conwed.com/cexp-

maintenanceandcleaning



### Sustainability

For your LEED projects, our products can help you qualify for different points depending on the product you choose. Contact us to learn more detailed information.

To view our certificate visit conwed.com/cexp-LEED.



### Warranty

3 years. Refer to Warranty for more details.

conwed.com/cexpwarranty

# Max size availabilities

- Standard core max size
- NAF (No-Added-Formaldehyde core) max size

Thickness	4'×10'	4'×12'	5'×10'	16 sqft
5/8"	•			
7/8"	•			
1 1/8"	۰	•	•	
1 5/8"	•			
2 1/8"	٥	•	•	
3 1/8"				• 0

# **Acoustic performance**

The NRC of the products are determined from an average of sound absorption coefficients, obtained from tests conducted according to ASTM C423 procedures in an NVLAP accredited laboratory.

HZ →	125	250	500	1000	2000	4000	NRC ↓
5/8"	0.04	0.22	0.60	0.97	1.07	1.04	0.70
7/8"	0.07	0.34	0.80	1.04	1.08	1.06	0.80
1 1/8"	0.08	0.46	0.95	1.07	1.06	1.01	0.90
1 5/8"	0.16	0.72	1.09	1.12	1.05	1.04	1.00
2 1/8"	0.27	0.90	1.11	1.06	1.04	1.10	1.05
3 1/8"	_	_	_	_	_	_	_