

All products made-to-order

Ceiling Panel Product

Finish




Durability

Conwed Panels are reliable, all-purpose acoustic solutions. Capable of multiple levels of durability, highly-customizable finishes, and mounting options, this product is suitable for schools, auditoriums, theaters, offices, and libraries: anywhere noise control is needed.

Foundations

New Dimensions Foundations (Unpainted)

Items to specify



Click for full specsheet conwed.com/specsheet-ceilingpanel-paint-a

Mounting type



Snap-on

Anchors

Paint

SHERWIN WILLIAMS



Resin

spots





Corners



Radius Square

Edge profile







Foundations | Painted products can be left unpainted, to be finished in the field.



Fire rating

Conwed products meet or exceed ASTM E84 standards for smoke development and flame spread on a component level.



Shapes

This product can be made into custom shapes for complex designs. Contact Customer Service for more info on how we can support your project.



Washable

Refer to the Maintenance & Cleaning Guide for more details.

conwed.com/cexpmaintenanceandcleaning



Sustainability

For your LEED projects, our products can help you qualify for different points depending on the product you choose. Contact us to learn more detailed information.

To view our certificate visit conwed.com/cexp-LEED.



Warranty

3 years. Refer to Warranty for more details.

conwed.com/cexpwarranty

Max size availabilities

- Standard core max size
- NAF (No-Added-Formaldehyde core) max size

Thickne	ess 4	4'×10'	5'×10'	16 sqft	
1"		0	•		
1 ½"		•			
2"		0	•		
3"				• 0	

Acoustic performance

The NRC of the products are determined from an average of sound absorption coefficients, obtained from tests conducted according to ASTM C423 procedures in an NVLAP accredited laboratory.

HZ →	125	250	500	1000	2000	4000	NRC ↓
1"	0.04	0.28	0.73	1.07	1.11	1.13	0.80
1 ½"	0.10	0.53	1.06	1.15	1.09	1.06	0.95
2"	0.11	0.79	1.16	1.15	1.09	1.12	1.05
3"	0.13	1.09	1.20	1.12	1.08	1.07	1.10