

Durability

New Dimensions

All products made-to-order

Conwed Tiles bring the best acoustic performance out of traditional drop-grid ceilings, whether they're in the original spec, or a retrofit. Schools, offices, and more can all benefit.

Items to specify



Mounting type

Fits in standard ceiling grid systems

Standard 15/16" Designer %16"

Paint



Foundations

Foundations | Painted products can be left unpainted, to be finished in the field

Hotmelt fabric adhesion

Provides superior bond strength lasting the lifetime of the product. Easily reactivated for field repairs and modification.

Edge profile



Lay-in square

Fire rating

Conwed products meet or exceed ASTM E84 standards for smoke development and flame spread on a component level.



Shapes

Click for full specsheet



Washable

Refer to the Maintenance & Cleaning Guide for more details.

conwed.com/cexpmaintenanceandcleaning



Sustainability

For your LEED projects, our products can help you qualify for different points depending on the product you choose. Contact us to learn more detailed information.

To view our certificate visit conwed.com/cexp-LEED.



Warranty

3 years. Refer to Warranty for more details.

conwed.com/cexpwarranty

Max size availabilities

- Standard core max size
- NAF (No-Added-Formaldehyde core) max size

Thickness	2'×8'		
ן"	• 0		
1 ½"	•		
2"	• 0		

Acoustic performance

The NRC of the products are determined from an average of sound absorption coefficients, obtained from tests conducted according to ASTM C423 procedures in an NVLAP accredited laboratory.

HZ →	125	250	500	1000	2000	4000	NRC ↓
1"	0.04	0.28	0.73	1.07	1.11	1.13	0.80
] ½"	0.10	0.53	1.06	1.15	1.09	1.06	0.95
2"	0.11	0.79	1.16	1.15	1.09	1.12	1.05