All products made-to-order








Conwed Tiles bring the best acoustic performance out of traditional drop-grid ceilings, whether they're in the original spec, or a retrofit. Schools, offices, and more can all benefit.

Finish

Durability

Acoustic Art

# Items to specify



Click for full specsheet

## Mounting type

Fits in standard ceiling grid systems

Standard 15/16" Designer %16"

### Custom Print Finish

### File requirements

Vector: AI, EPS, SVG, PDF Raster: JPG, TIFF, PDF, PSD Resolution: 300 DPI Max file size: 1 GB

Click for full print requirements

## Edge profile



Lay-in square

Edges are painted with a black painted finish.

### Fire rating

Conwed products meet or exceed ASTM E84 standards for smoke development and flame spread on a component level.



## **Shapes**



### Cleanable

Refer to the Maintenance & Cleaning Guide for more details.

conwed.com/cexpmaintenanceandcleaning



### Sustainability

For your LEED projects, our products can help you qualify for different points depending on the product you choose. Contact us to learn more detailed information.

To view our certificate visit conwed.com/cexp-LEED.



### Warranty

3 years. Refer to Warranty for more details.

conwed.com/cexpwarranty

# Max size availabilities

- Standard core max size
- NAF (No-Added-Formaldehyde core) max size

Thickness	2'×8'
] ½"	• •
2 1/8"	• •

Larger images can be spread over multiple panels

Copyright disclaimer: Users acknowledge that all images, names, dates, and other content added to their design are correct and they own all copyrights to them or have full authorization to use them.

# **Acoustic performance**

The NRC of the products are determined from an average of sound absorption coefficients, obtained from tests conducted according to ASTM C423 procedures in an NVLAP accredited laboratory.

н	Z→	125	250	500	1000	2000	4000	NRC ↓
1	1/8"	0.09	0.48	0.93	1.13	1.10	1.03	0.90
2	1/8"	0.26	0.96	1.17	1.18	1.11	1.02	1.10