



Eurospan

Rather than limiting your architectural design, Eurospan gives you the tools to create your own acoustic solution that can replace a wall or ceiling entirely. Made from only three components, Eurospan can be entirely discrete, or be the centerpiece of your space.


Ceiling

Eurospan can replace entire ceilings with a smooth surface, and still accommodate for extrusions such as can lights and sprinkler systems. If used in initial construction, Eurospan Ceilings only need a deck to mount to before installation. The system can additionally be retrofitted onto existing ceilings, for rooms with unexpected levels of noise.

Core construction

Comprised of three basic components: a fiberglass acoustic core, perimeter tension track and outer textile covering. This seamless product uses a high-performance integrated acoustical core with a white matte covering. Tension tracks arranged around the perimeter hold an acoustically transparent textile which can be stretched over areas 16' wide.

1. Tension track
2. Fiberglass core
3. Fabric finish



Acoustic performance

The NRC of the products are determined from an average of sound absorption coefficients, obtained from tests conducted according to ASTM C423 procedures in an NVLAP accredited laboratory.

HZ →	125	250	500	1000	2000	4000	NRC ↓
1 ½" thickness	0.13	0.32	0.76	1.00	1.13	1.07	0.80
EOS 1 ½" thickness	-0.01	0.33	0.91	1.09	1.03	0.85	0.85

Eurospan Ceiling Finishes

Eurospan PRIME

Prime is our specially-formulated fabric, perfect for stretch systems. Excellent weight, color, and texture. Available in white, black, and custom-dyed color.

EOS

EOS is a washable white stretch fabric that is fully compatible with the Eurospan system, with slight changes in NRC performance.

Compatible Brands

Carnegie DESIGNTEX maharam Knoll Guilford of Maine


Max size availabilities

System can be furred out to desired thickness.

System Thickness	Eurospan Fabric Width 16'*	Length 40'+
1 ½"	✓	✓
EOS 1 ½"	✓	✓

NAF Core Thicknesses also available in No-Added-Formaldehyde cores are indicated with red checkmarks.


*Designer fabric widths apply.



Edge details

Available choices include:

- Square



Mounting

Standard mountings:

- Square perimeter, edge wrap, outside corner, & mid-joint track



Fire Rating

Conwed products meet or exceed ASTM E84 standards for smoke development and flame spread on a component level.



Standard Durability

This product has a durable core construction, ideal for out-of-reach areas.



Shapes

This system can be made into different shapes, and bend over an axis using different track pieces. Contact Customer Service for more info on how we can support your project.



Washable

Refer to the Maintenance & Cleaning Guide for more details.
conwed.com/cexp-maintenanceandcleaning



Warranty

10 years. Refer to Eurospan Warranty for more details.
conwed.com/cexp-warranty-eurospan

Sustainability initiatives



LEED®

For your LEED projects, our products can help you qualify for different points depending on the product you choose. Contact us to learn more detailed information. To view our certificate visit conwed.com/cexp-LEED.

Disclaimer of liability: Technical information contained herein is furnished without charge or obligation and is given and accepted at recipient's sole risk. Conditions of use may vary and are beyond our control, and because of this Conwed makes no representation about, and is not responsible or liable for, the accuracy or reliability of data associated with particular uses of any product described herein.